

Declaration of Performance

No. 30-10848/2 (ver. 2)

Camo edge fastening, Trim head Deck Screw, A4 stainless steel


Intended use or uses of the construction product according to EN 14592+A1:2012	
Authorised Representative	Kyocera Senco Netherlands B.V. (www.senco-emea.com)
Generic type	Dowel-type fastener for use in loadbearing timber structures
Unique identification codes	345219S ; 345224S ; 345238S ; 345239S ; 345244S ; 345248S
Material	A4 (CRC III)
Under AVCP System	3
Notified Body	NB 1015

Declared performances according to EN 14592+A1:2012			
Essential Characteristics			Performance
Nominal diameter for calculation acc. to EC5 (d)		[mm]	3,9
d_h	Head diameter (Trim)	[mm]	5,0
d_1	Minor diameter	[mm]	2,85
$M_{y,k} (M_{y,Rk})$	Characteristic Yield Moment	[Nmm]	2100
$f_{ax,k}$	Characteristic Withdrawal parameter ($\rho_a = 350 \text{ kg/m}^3$)	[N/mm ²]	13,0
$f_{head,k}$	Characteristic head pull-through parameter ($\rho_a = 350 \text{ kg/m}^3$)	[N/mm ²]	23
$f_{tens,k}$	Characteristic tensile capacity	[N]	3500
$f_{tor,k} / R_{tor,k}$	Torsional ratio ($\rho_a = 450 \text{ kg/m}^3$)	[-]	> 1,5
Reaction to fire (EN 13501-1)			A1
Durability			Stainless Steel A4 (CRC III) , Service Class 1, 2 & 3 acc. EN 1992-1-1

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of Camo Fasteners by:

Place and date of issue: Grand Rapids (MI), 03-11-2021



Todd Schwartzkopf

Product Design Engineer
2964 Clydon SW
Grand Rapids, Michigan, USA 49519